

Lecture 01 – Data Mining

AMOD-5440

Kat Clark

Trent University

2026-09-11

Welcome Information

Contact Details

- **Me:** Dr. Kat Clark
- **Email:** katclark@trentu.ca
- **Office:** ENW 332

Digital Tech & Links

- **Blackboard**: official grades, class-wide communications, slides and video links, ~~assignment code submission~~.
- **Crowdmark**: Assignment release and PDF submissions.
- **RStudio**: learning to **do** statistics and data analysis (5 assignments) - preferably your own computer, but <https://sage.trentu.ca/> if not

RStudio

The **R** programming language and interface is **the** language of statistics in the 21st century.

- You will be learning (more about how) to do **data analysis** using **R** in this class
- Many ways to use RStudio - recommend you bite the bullet and install it on your own computer if at all possible (instructions on Blackboard). If not, our **server** is an option.

Crowdmark

Assignments will be conducted with Crowdmark.

- You will get an email from Crowdmark when assignments are released.
- PDFs must be uploaded to Crowdmark.
- You will also be submitting your R code on Crowdmark.

Course Overview

Posted Material

- Lectures: First 2 hours of class on Friday afternoons. Slides posted before class.
- Live Coding Labs: Third hour of class. We will code together and the files will be posted after class.

Text

- The textbook we are using is a Springer book, and is considered **the** standard introductory reference for data mining algorithms.
- Thankfully, while you can buy a physical copy for \$65-85 on Amazon, there's a completely free PDF available from the authors' [website](#).
- If you want a physical copy, have at it! Otherwise, save your money.

Things Worth Marks

- Assignments: $5 \times 10\% = 50\%$
- In-class quizzes: $5 \times 2\% = 10\%$
- Midterm: 90 minutes in class on October 23rd. 15%. Covers material from weeks 1-6
- Final Exam: During exam period. 25%. Cumulative

R Assignments (50%, 5 x 10%)

- Due on Thursdays in weeks 3, 5, 7, 10, and 12.
- The R assignments are designed to assess your learning of the material from the previous two weeks.
- Each one will examine some algorithms, and analyze some real data.
- The reports will be written in Quarto, and turned in as a PDF on Crowdmark.
- The Quarto file will be submitted on Crowdmark.

Paired Assignment Quizzes (10%, 5 x 2%)

- During class the day following the assignment
- Will be short ~5-10 minutes.
- Hand-written, closed-book
- Very straightforward
- Tests if you know your own submission
- While each quiz is worth only 2%, it will cap your assignment grade.

Quiz Cap

Quiz Score	Maximum Assignment Report Grade
80–100%	No cap
70–79%	85%
60–69%	75%
Below 60%	65% and subject to instructor review

Midterm (15%)

- The midterm will take place in class on October 23rd
- It is expected to take 90 minutes.
- It will be hand-written.
- Crib sheet allowed (details given later)
- The midterm will cover material from weeks 1-6

Final Exam (25%)

- The final exam will be scheduled by the registrar
- Same rules as the midterm
- The exam is cumulative

How to Get Help

- Read the textbook
- Google is surprisingly helpful for learning R stuff - there's a huge wealth of materials out there for beginners
- Lots of data mining / stat learning blogs out there - **warning** can be hard to wade through if you don't have experience
- Email me
- Schedule an office hour

Generative AI Tools: Overview

- Policies vary by course & instructor
- Examples: ChatGPT, Copilot, Claude, Gemini
- Use to *troubleshoot*, not do your work for you.
- Always ensure work submitted reflects **your own** decisions and understanding

Appropriate and Inappropriate Uses

Appropriate Uses:

- Debugging & syntax correction
- Identifying errors in code
- For example:
 - You keep encountering an error when rendering your document. You try to fix the problem but come up empty.
 - You paste the error code in Copilot and it tells you that you have an extra comma. You fix it.
 - You make sure to write a note in your assignment about which AI you used and how.

Appropriate and Inappropriate Uses

Inappropriate uses:

- Direct file-modifying AI tools (e.g., Copilot, Gemini Code, Claude Code, Posit Assistant)
- Copying/pasting AI-generated solutions directly
- Using AI to complete graded work
- Asking AI to interpret output or suggest what to do next
- “Consulting” AI to make decisions, e.g. for which parameters or model to choose

Violations: Academic Integrity

- Improper AI use.
- Copying code, solutions, or write-ups without attribution
- Uploading course materials to:
 - AI tools (e.g., ChatGPT)
 - Chegg, CourseHero, or similar
- If unsure, **ask your instructor**
- A first offence will result in a **zero** on the relevant assessment. Subsequent offences will result in failure of the course.

Key Takeaways

1. Use AI to **troubleshoot**, not to replace your own work and/or thinking
2. Always **verify** AI information with trusted sources
3. Attribute help from AI & online resources
4. Protect course materials & respect instructor permissions

Data Mining

Statistical Learning

What IS Data Mining?

Data mining, a.k.a. *statistical learning* refers to a set of tools for **understanding data**. These tools can be classified as:

- **supervised**: involves building a statistical model for predicting, or estimating, an output based on one or more inputs.
- **unsupervised**: there are inputs but no supervising output; nevertheless we can learn relationships and structure from such data.

Linear Models

- In previous courses, you may have seen classes of **linear models**, often just called *regression* or *multiple regression*, when the inputs and outputs are numeric.
- You may also have seen **ANOVA**, which is a specific class of linear model where the inputs are categorical.
- Both of these fall under the classification of **supervised statistical learning**.

Some Language

Almost all models we will cover this semester share some common language.

- **input variable**: also called predictors, *independent* variables, features, or just variables
 - typically denoted by X
 - if you have more than one, X_1, X_2 , through X_p
- **output variable**: also called the response, or *dependent* variable
 - typically denoted by Y

Mathematical Notation

- We will do our best to keep the mathematical notation to a minimum, but sometimes you'll want to read the textbook, and puzzle out what it is trying to say.
- If we assume that we observe some Y which is quantitative, and have p different predictors, $X_1, X_2, \dots, X_p$, then what we are interested in is a **relationship** between these.

Some Notation

- Generically, we might write:

$$Y = f(X) + \varepsilon$$

where the unknown function f represents the relationship between the X predictors and the response Y .

- We assume there is some error in the **observations**, so that we cannot capture $f(\cdot)$ perfectly: this is ε .

Multiple Linear Regression

In multiple linear regression, the unknown function is just summation:

$$Y = \beta_0 + \underbrace{\beta_1 X_1 + \dots + \beta_p X_p}_{f(X)} + \varepsilon,$$

such that Y is related to the X s via a linear combination, the sum of each of the X s multiplied by a scale factor β_i , for $i = 1, 2, \dots, p$.

Note: you will never have to do mathematical derivations in your assignments. Each of these X s corresponds to a vector of observations in $\mathbb{R}$, as does the Y .

Example, R

$$Y = 0.5 + 1.0X_1 + 2.5X_2 - 1.3X_3 + \varepsilon$$

```

1 library(dplyr)
2 dat <- data.frame(x1 = rexp(20),
3                   x2 = rexp(20) + 2,
4                   x3 = rexp(20) - 1)
5
6 dat <- dat |>
7   mutate(y = 0.5 + 1.0 * x1 + 2.5 * x2 - 1.3 * x3 + rnorm(20))
8
9 mod <- lm(y ~ x1 + x2 + x3, data = dat)
10
11 mod |> coefficients()
```

$\varepsilon \sim N(0, 1)$

(Intercept)	x1	x2	x3
1.281539	1.244548	2.221301	-1.335892

Example, R

- We generated some fake data, built a relationship between X and Y , then asked a **supervised learning** algorithm to estimate the relationship.
- You can see that we **estimated** the coefficients on the previous slide, in the R code provided.
 - $\beta_0 = 0.5$, we estimated 1.282
 - $\beta_1 = 1.0$, we estimated 1.245
 - $\beta_2 = 2.5$, we estimated 2.221
 - $\beta_3 = -1.3$, we estimated -1.336

Estimating

Why Estimate f ?

- Recall that our relationship between the X predictors and the response Y is given by:

$$Y = f(X) + \varepsilon.$$

- Why** would we want to estimate f ?
- There are two main reasons: for **prediction**, and for **inference**.

Prediction

When the outcome is known for past observations, we can use those data to build a model and make predictions for new observations.

Example: Use information from previous patients and their surgical outcomes to predict the probability of a favourable outcome for a new patient.

Past Data $\longrightarrow$ Model $\longrightarrow$ Prediction for New Data

Goal: Accurately predict the response variable Y for future observations.

Inference

When the goal is inference, we are interested in understanding the **relationship** between the predictors X and the response Y , not just making accurate predictions.

Example: Suppose we want to understand how age, smoking status, and exercise habits affect the probability of a favourable surgical outcome. In this case, we care about *which variables matter* and *how they affect the outcome*.

$$X \longrightarrow \text{Model} \longrightarrow Y$$

Goal: Understand and explain the relationship between X and Y , rather than treating the model as a black box.

In many scientific studies, explanation and understanding are more important than prediction.

Prediction

Notation for Prediction

- Let's start with the first goal: prediction.
- We use “hat” notation to refer to predictors and prediction. So, we would say that our prediction of Y is $\hat{Y}$:

$$\hat{Y} = \hat{f}(X),$$

where $\hat{f}$ is our prediction (“estimate”) of the unknown function f that links the inputs X to the output Y .

Examples of Settings for Prediction

- blood chemistry & patient risk
- rental price for an apartment with specific characteristics (“market value”)
- grade you should have gotten on your final exam, if you’d had the chance to write it (aegrotat standing)
- potential income based on education, seniority, field of work
- fitness of a species under constraints in the environment

Accuracy

- We're estimating an unknown function, but *estimating* could be rephrased as *educated guessing*.
- Technically speaking, **any** guess is an estimate! And not necessarily a **good** one!

Example: the “stopped clock” estimator. If you ask me what time it is, and I always respond 11 o'clock, I will almost always be wrong. But it **is** an estimate, and it **will** be correct ... sometimes. Namely, at 11am and 11pm!

- Some estimators are clearly better than others.
- Ideally, would like to estimate *close* to the true value, *most of the time*.
- However, some error is unavoidable.

Errors in Prediction

Even with the best possible model, predictions are not perfect. Prediction error is often divided into two components: $\mathcal{E}$

Reducible Error

Error that can be decreased by improving the model, collecting more data, or choosing better predictors.

Example: If I estimate the current time by always saying “11:00”, my predictions will be poor. Looking at a clock provides a much more accurate estimate.

Errors in Prediction

Irreducible Error


Error that remains even when the best possible model is used.

Example: A clock may be slightly inaccurate, or it may not display seconds. Even with access to the clock, some uncertainty remains.

Key idea: Reducible error comes from our estimate of f , while irreducible error comes from the random error term ε , which cannot be eliminated.

General Points

- Because this is a survey course of data mining methods, we will cover a lot of different approaches.
- Each approach/algorithm has its strengths, and its weaknesses.
- Always consider more than one factor when being told something is “the best at X” - there’s almost always more to the story.



General Points (Continued)

- For example, certain Machine Learning algorithms are very strong at prediction, as measured by the accuracy of the method on a test set (a strength).
- However, once you go outside the realm of the test/train data, the methods can perform very poorly.
- This is a weakness. It does not mean they are not useful, simply that they are limited, as all things are.

Our Objective for Prediction in General

- Our objective, any time we are predicting things, is to reduce the Reducible Error as much as is feasible.
- That means we will have the best prediction we can, under the constraints of the data, and our available skills.
- This course will hopefully broaden your skill-base so that you have access to significantly more skills, which should make your scientific predictions significantly more capable.

A Small R Example

Using the data from before, X_1, X_2, X_3 which are linearly combined (with noise) to make Y . Let's try to predict the value of Y at a particular combination of X s.

```
1 predict(mod, newdata = data.frame(x1 = 2, x2 = 1, x3 = -1))
```

```
1
7.327827
```

What is the true, average value?

$$Y = f(2, 1, -1) = \beta_0 + \beta_1 X_1 + \beta_2 X_2 + \beta_3 X_3 = 0.5 + 1.0(2) + 2.5(1) - 1.3(-1) = 6.3$$

A Small R Example (Continued)

- We know we used the “right model” (multiple linear regression is the perfect fit for this data).
- The difference between the true value of 6.3 and our predicted value of 7.33 is **irreducible error**.
- This is due to the ε .

Inference

Inference

What are some of the questions we might ask about the function $f(\cdot)$?

- which predictors are associated with the response?
- what is the relationship between the response and each predictor?
- can the relationship between Y and each predictor be adequately summarized using a linear equation, or is the relationship more complicated?

How Do We Do It?

- Estimating f , the goal of inference, is **hard**.
- There are many methods available that do some aspect of this, but all are subject to **constraints**.
- This kind of problem is sometimes referred to as **underdetermined** - this means there just isn't enough information available to estimate $f(\cdot)$ without making assumptions and simplifications.

What Kinds of Approaches?

- Primarily, we divide our approaches to estimating $f(\cdot)$ into two classes: **parametric** and **non-parametric**.
- Both approaches obtain, from the available data, a **training data** set.
- We use this data to **train** our method on how to estimate $f(\cdot)$.
- In doing this, we apply the method to find an educated guess $\hat{f}$ such that $Y \approx \hat{f}(X)$ for any observation (X, Y) .

Parametric Methods

These are what you think of when you think of statistical methods, especially the family of linear models.

1. Make an assumption about the form of $f(\cdot)$, e.g., assume f is linear in X , e.g. linear regression– this is a tremendous simplification.
 2. Use a procedure that takes the training data, and trains (or “fits”) the model. Typically, we use software for this.
- The **parametric** part of the name comes from the process whereby we reduce the problem from estimating f down to only estimating a set of parameters.
 - In linear regression, the parameters are the $\beta_0, \dots, \beta_p$.

Non-Parametric Methods

- Non-parametric methods do not make explicit assumptions about the functional form of $f(\cdot)$.
- They still have some sort of framework in place (remember: it's impossible to estimate f without something!), but instead of assuming things about the functional form, they seek an estimate of f that is as close to the data as possible without being either too wiggly or too flat.
- The typical restriction we require for non-parametric fits to data is that the resulting fit (estimate) be “smooth”.
- This is somewhat vague, and deliberately so. We'll come back to this topic in a few weeks.

How to Choose ...

- This semester, we will be looking at a variety of methods.
- Some are parametric, some are non-parametric.
- Some are highly restrictive and have strong assumptions;
- Others are very free, and have only weak or limited assumptions.
- How do you decide what is appropriate for your data?

Trade-Offs: Accuracy and Interpretability

There are two, or maybe three, considerations when choosing a method.

1. Accuracy (or Flexibility):

- how restrictive are the assumptions to the possible outputs of the model?
- Can the chosen model represent a wide variety of possible relationships?
- High accuracy/flexibility examples: deep learning, neural networks, SVMs;
- Low accuracy/flexibility examples: Lasso, least squares, GAMS

Summarized as “how accurately can the model reproduce the given data?”.

Trade-Offs: Accuracy and Interpretability

2. Interpretability:

- understanding the structure and implications of the model framework is important for inference and scientific understanding.
- How well can the model fit be interpreted to give scientific information?
- High interpretability examples: Lasso, least squares;
- Low interpretability examples: deep learning, neural networks

Summarized as “is there a direct interpretation of the coefficients of your model which can be translated into scientific language?”

Trade-Offs

- When **prediction** is your goal, and you don't actually care about the interpretability of the model itself, complex and uninterpretable models such as neural nets can be highly powerful.
- When **inference** is your goal, you do care about interpretability of your model, so less-complex and more inflexible statistical models have advantages.
- We will spend most of this course talking about these trade-offs, especially once we have a few models developed and can discuss how and why you might want to use them.

Assessing Model Accuracy

Evaluate Performance & Make Decisions

- If we want to compare some methods, one to another, or even evaluate the performance of a single method, we need **metrics**: ways of measuring how well predictions actually match observed data.
- Formally, we want to **quantify** how close the predicted response value for a given observation is to the actual, true, response value for that observation.
- In math, we want to somehow measure $y - \hat{y}$: the difference between the true y and the predicted $\hat{y}$.

Choosing a Metric

- We will talk about this a lot, actually - the way of choosing how to measure that difference varies tremendously across methods.
- Choosing a different way of measuring it often gives an entirely different method!
- Some people's careers have been made on coming up with a clever choice...

Squared Error

- One of, if not the, oldest methods available is the **squared error**.
- We want our metric to quantify how close, overall - that is, across the n data points you have.
- So if you have some predictions that are + and some that are -, they can balance out, and indicate the difference is 0, when it is not!

$$\frac{\sum (y - \hat{y})}{n} \quad \text{usually } 0$$

$$\frac{1}{n} \sum (y - \hat{y})^2$$

MSE

So, instead, we square the differences. This leads to **mean squared error** (MSE):

$$\text{MSE} = \frac{1}{n} \sum_{i=1}^n \left(y_i - \hat{f}(x_i) \right)^2$$

y_i

This is the **mean** (average) across the i data points of the squared difference between y_i and $\hat{f}(x_i) = \hat{y}_i$.

This is what is used to give us regression!

How to Apply This?

- There is a key difference between how well a model works on training data (data you've "seen before"), and how well a model works on test data ("new data").
- We don't usually care **that** much about how well a model fits to training data, because ... we have all of that data!
- Instead, what we care about is how well a model fits to data we've never seen, because predicting those situations is why we modelled in the first place.

How to Apply This? (Continued)

- In practice: you may not have test data. There are ways around this.
- We can split the data we **do** have into two sets, train on the “training” one, and then compute the MSE or similar metrics on the “test” one. This is the traditional approach in machine learning.
- Or, we can get fancy ... more on this later in the term!

Course Set Up for Next Week

First Major Topic

- Our first major topic will be a revisit of linear models.
- We will consider simple linear regression, multiple linear regression, and the concept of transformation of variables.
- It is intended to be a refresher, and give you two weeks to get your feet under you and ready to learn new ideas.

Readings

- The material of this first week is Chapter 2 of ISLR, inclusive.
- Some parts were skipped or only skimmed (esp. 2.1.5, 2.2.2 and 2.2.3), and will be covered “as needed” (i.e., in a couple of weeks).
- Chapter 1 was also mentioned in part, but if you read it, just skim and look for high points.
- The mathematical notation at the end of Chapter 1 is important if you want to understand the equations we will use, although that isn’t strictly required for success.
- The material of the second week, and the first major topic, is Chapter 3, sections 3.1-3.3.3 inclusive, if you would like to (and I recommend it!) read ahead on the material.

Today's Lab

- We will be working through a refresher on R and Quarto, and ensuring everyone is set up to be able to do their work in a good environment.
- We will use some data from ISLR that was mentioned in Chapters 1 and 2, and recreate some of the figures!